## **FSI** ACM-WAVE-PLUS

## **Directional Wave and Current Meter**

Wave Direction and Height with vector-averaged 3D Current Speed and Direction in a Single Instrument

### Enhanced Design, Performance, Specifications

The *ACM-WAVE-PLUS* from Falmouth Scientific, Inc. provides wave direction, wave height, and other wave statistics by combining FSI's enhanced ACM-PLUS acoustic current meter technology with a highaccuracy, micro-machined silicon pressure sensor. The instrument can be deployed in a multiple-mode format to allow periodic burst sampling of wave data as well as long-term averaging.

The *ACM-WAVE-PLUS* includes advanced standard features such as **extended on-board data memory**, fast download capability, high accuracy real-time clock, and high speed data sampling.

The **ACM-WAVE-PLUS** comes complete with FSI's Windows-based **ACMProPLUS** software for system configuration and data download, as well as our **WavePost** software for graphics display and advanced post-processing.

The device may also be equipped with an optional CTD module, and can be configured to log up to two analog inputs from external sensors (e.g., DO, OBS, Fluorometer, Transmissometer).



FSI ACM-WAVE-PLUS shown with optional CTD and 5-ton frame

#### FEATURES

- High-accuracy wave data, precise pressure sensor
- Built-in 3-Axis ACM with excellent low-velocity resolution
- Electronic magneto-resistive compass, 2-axis tilt sensor
- Fast Data Sampling up to 5 Hz; Fast Data Download
- Long-term data logging to 2 GigaByte internal memory
- Built-in *High Accuracy* real-time clock
- 1.5-ton working strength mooring frame standard; optional 5-ton mooring frame
- Optional conductivity, temperature, pressure sensor package (CTD) may be added

Falmouth Scientific, Inc. www.falmouth.com



# SPECIFICATIONS

ensors		SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NO		
Parameter	Туре	Range	Accuracy	Resolution
Pressure (Wave Height)	Silicon Micro-machined	0-50 PSIA (23m max depth)	±0.01% full scale	0.145 x10 <sup>-3</sup>
Velocity	Acoustic	0 to 600 cm/s	≤ 1%±0. 5 cm/s	0.01 cm/s
Direction	3 Axis Magnetometer	0 to 360°	±2°	0.01°
Tilt	2 Axis Accelerometer	0 to 30°	0.5°	0.01°
Temperature	Semiconductor	-2 to 35°C	0.5°C	0.01°C

### **Optional CTD**

	Range	Accuracy	Resolution	Stability
Conductivity (mS/cm)	0 to 70	±0.01	.001	±0.0005 per month
Temperature (Celsius)	-5 to 32° ITS-90	±0.01°	.001°	±0.0005° per month
Pressure (dBar)	0 to 200 dBar	±0.1% full scale	0.01% full scale	±0.01% per month

#### Instrument

External Power:	8 to 32 VDC	
Current Draw:	Typical 60 mA at 1 Hz sample rate; Sleep 1.0 mA battery, 3.5 mA external power	
Battery Power:	Alkaline 5 D Cell Welded Pack, 10 AHR	
Internal Memory:	2.0GB Standard	
Sample Rate: Vector Averaging Period: Real Time Clock: Sampling Modes: Clock Stability:	5 Hz Maximum User Selectable up to 59 Min:59 Sec Programmable High Accuracy Sampling / Low-power Mode Continuous, Interval, and Delayed Start (continuous or interval) +/- 2ppm (0-40 degrees C); +/- 4ppm (-40 degrees C to +85 degrees C)	
Optional Input Channels:	Two (2) 0-5V DC Input Channels with 12 bit A/D resolution available for external sensor input (Regulated 12 VDC, 1.5W provided to power external sensors)	
Depth Rating/Physical Material:	200 Meter Epoxy Housing Standard, P/N: ACM-WAVE-PLUS	
Mooring Frame:	1.5 Ton Rated 316 Stainless Steel Mooring Frame (Standard); 27" x 9.25" square (approx.) 5 Ton Rated 316 Stainless Steel Mooring Frame (Optional); 39" x 9.4" square (approx.)	





Example Wave Directional Energy (left) and Pressure Analysis (right)

NOTE: FSI Does not provide the wave analysis Software

4 April 23